

Date of Deposit: October 30, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Assistant Commissioner For Patents, Washington, D.C. 20231

By: Keith Johnson

10-31-00

A
JC853 U.S. PTO
09/699820
10/30/00

10/30/00
U.S. PTO
C
O
R
P
O
R
A
T
I
O
N

Attorney's Docket No. XER 2 0329
D/A0125UTILITY PATENT APPLICATION TRANSMITTAL LETTER

(Only for nonprovisional applications under 37 CFR 1.53 (b))

Assistant Commissioner
for Patents
Washington, D.C. 20231

Transmitted herewith for filing in the patent application of:

Ying-wei Lin and Jeng-nan Shiau

Entitled: COLOR TO BLACK AND WHITE CONVERTER

Enclosed are:

- [X] 18 sheets of specification, 4 sheets of claims, 1 sheet of Abstract.
- [X] 12 sheets of drawings, Figures 1-12.
- [X] an assignment of an invention to XEROX CORPORATION (and transmittal therefor).
- [X] a Declaration and Power of Attorney for Patent Application.
- [X] Information Disclosure Statement and PTO-1449
- [] Preliminary Amendment

CLAIMS AS FILED

| FOR | NO. FILED | NO. EXTRA | RATE | FEE |
|--------------------|-------------------------|-----------|-----------------------------------|-----|
| TOTAL CLAIMS | 20 - 20 = | 0 | [XX] \$18 LARGE [] \$09 SMALL | \$ |
| INDEPENDENT CLAIMS | 3 - 3 = | 0 | [XX] \$80 LARGE [] \$40 SMALL | \$ |
| BASIC FEE | [XX] LARGE ENTITY \$710 | [] | SMALL ENTITY \$355 | |
| | | | TOTAL FILING FEE \$ 710.00 | |

Please charge Deposit Account No. 24-0037 in the amount of \$ 710.00.

The Commissioner is hereby authorized to charge any additional fees which may be required at any time during the prosecution of this application without specific authorization, or credit any overpayment to Deposit Account No. 24-0037.

A check in the amount of \$ _____ to cover the filing fee is enclosed.

Attorney of Record
Joseph D. Dreher
Reg. No. 37,123
FAY, SHARPE, FAGAN,
MINNICH & MCKEE, LLP
1100 Superior Avenue
Seventh Floor
Cleveland, Ohio 44114-2518
(216) 861-5582

October 30, 2000
Date

COLOR TO BLACK AND WHITE CONVERTER5 **BACKGROUND OF THE INVENTION****1. FIELD OF THE INVENTION**

The invention relates to the art of image rendering. It finds application where color images are rendered with a single colorant. For example, the invention finds application in repro-graphic machines where a color image is scanned and then transformed for rendering so that single colorant (black and white) copies of the color image can be made. The invention finds further application in general-purpose computing devices such as personal computers and business graphics authoring devices. In the latter devices, color images such as bar and pie charts are created in color and displayed on a computer display and then are printed on black and white printers through the use of the invention. All these devices and devices like them are referred to herein as image processors.

2. DESCRIPTION OF RELATED ART

Communicating concepts and ideas to others can be difficult. One method often used to communicate ideas to a group of people is to make a visual presentation. In a visual presentation, images such as charts, graphs and photographs are often displayed before the audience while the speaker explains and describes the significance of the images. Alternatively, the images can act as summaries of an associated speech. Typically, the images are presented in color. Color often adds to the impact and clarity of an image. For example, a pie chart or a bar graph is easier to read if its various sections are presented in different colors.

Copies of visual presentation material are often distributed to the audience members. The distributed materials serve to document the presentation. The distribute material can help audience members follow the presentation and can serve as study aids and/or reference material.

Unfortunately, it can be impractical or prohibitively expensive to distribute a large number of color copies of presentation material. Furthermore, in some cases,

color reproduction equipment is not readily available. In these cases, the color images are often reproduced in black and white.

Creating black and white versions of color images can be problematic. Typically, a great deal of information is lost in the conversion to black and white. For example, typical, color image authoring devices can produce over sixteen million different colors, while typical black and white rendering devices can only produce two hundred fifty six shades of gray. Obviously, a great number of colors must be mapped to each level of gray. Therefore, portions of a color image that are quite obviously different colors can appear to be the same color when the image is rendered in black and white. When the image portions in question are, for example, different sections of a pie chart, this loss of information can render the pie chart useless.

Attempts have been made to alleviate this problem by using texturing to increase the number of ways colors can be represented in a black and white image. Typically, under these strategies, the conversion to black and white is accomplished by dividing colors into a finite number of bins and assigning a different halftone pattern to each of the bins. This approach can preserve more information from the color image. However, this approach can also lead to abrupt transitions in the black and white image. Where colors in the original image smoothly blend from one color to another, the blend in color can cross a bin boundary, resulting in a sudden shift in a halftone pattern or level. This problem is particularly pronounced when colors are near neutral or gray. This situation can be further aggravated by the presence of noise in the image. For example, a subtle jitter or shift in the color in a photograph of a person's face can be transformed into dramatic changes in halftone patterns if the jitter or shift is across one or more bin boundary.

Therefore, a method for rendering a color image in black and white is desired that preserves more of the information present in a color image. Furthermore a method is desired that accurately portrays smooth or subtle transitions in color as equally smooth or subtle transitions in texture.

30 BRIEF SUMMARY OF THE INVENTION

To those ends, a method for generating a single colorant version of a multicolor image, that preserves color information in the image, has been developed.

The method comprises the steps of generating a continuously variable screening tool operative to provide a unique texture corresponding to each hue and saturation in the color image, and transforming the multicolor description of the image through the continuously variable screening tool thereby creating a single-colorant description of
5 the image.

In some embodiments, the step of generating a continuously variable screening tool further comprises defining a neutral screen associated with neutral color, defining a plurality of primary screens associated with a plurality of hues from the multi-colorant color space and generating a set of blended screens associated with a set of
10 remaining hues by performing a weighted blend between nearby screens.

An image processor operative to use the method to render a single colorant version of a multicolor image comprises a continuously variable screening tool generator operative to generate a different screen texture for every hue and saturation in the multicolor image.

15 In some embodiments of the image processor, the continuously variable screening tool generator further comprises a reference screen storage device operative to store a set of predetermined reference screen patterns in association with locations within a color space and a screen blender operative to access the screen storage device and use the reference screens to calculate screen patterns for colors in the multicolor
20 image that do not correspond to locations in the color space associated with the reference screens.

One advantage of the present invention resides in the ability to generate black and white versions of color images that preserve information coded in even subtle color differences.

25 Another advantage of the present invention is found in the ability to render different colors having the same luminance so that they can be distinguished in a black and white version of the image.

Yet another advantage of the present invention stems from the fact that it requires very little extra system resources such as, for example system memory.

30 A further advantage of the present invention is that it requires only a minimal amount of extra calculation and therefore can be carried out very quickly.

Still other advantages of the present invention will become apparent to those

skilled in the art upon a reading and understanding of the detail description below.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The invention may take form in various components and arrangements of components, and in various steps and arrangements of steps. The drawings are only for purposes of illustrating preferred embodiments, they are not to scale, and are not to be construed as limiting the invention.

FIGURE 1 is a black and white version of a color map rendered through the use of a prior art method by a prior art image processor;

10 FIGURE 2 is a black and white version of a color pie chart rendered through the use of a prior art method by a prior art image processor;

FIGURE 3 is a flow chart outlining a method to preserve color information in a single colorant version of a multicolor image;

15 FIGURE 4 is a chart showing reference screens, used in some embodiments, to carry out a step in the method of FIGURE 3, the reference cells being distributed about a color space to show an assigned relationship between the reference screens and the color space;

FIGURE 5 shows numerical representations of some of the reference screens of FIGURE 4;

20 FIGURE 6 shows numerical representations of an intermediate and a final version of a calculated blended screen based in part on the reference screens of FIGURE 5;

25 FIGURE 7 is a diagram showing, in graphical form, the calculation of the blended screen of FIGURE 6. FIGURE 8 is a chart showing the reference screens of FIGURE 4 in relation to the color space of FIGURE 4 and to a set of calculated blended screens; FIGURE 9 is a block diagram illustrating processing flow in an embodiment of the method of FIGURE 3;

FIGURE 10 is a black and white version of a color map rendered by the method outlined in FIGURE 3;

30 FIGURE 11 is a black and white version of a color pie chart rendered by the method outlined in FIGURE 3; and

FIGURE 12 is a block diagram of an image processor operative to carry out

the method of FIGURE 3.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings wherein the showings are for purposes of illustrating the invention and not for purpose of limiting the same thereto, FIGURE 1 illustrates a black and white or single colorant version of a color map of Africa 110 produced by a prior art image processor by transforming colors to shades of gray. The transformation is accomplished, for example, by measuring or calculating a lightness level for each color in the image and then producing a shade of gray corresponding to each lightness level. This technique has drawbacks. For example, in the original color image (not shown), The Western Sahara and Morocco are clearly separate countries. The Western Sahara is rendered in yellow and Morocco is depicted in a light shade of cyan. However, in the prior art black and white version of the image of Africa 110, The Western Sahara 114 is almost indistinguishable from Morocco 118. Furthermore, in the prior art image of Africa 110, Equatorial Guinea 122 is indistinguishable from its neighbor Gabon 126 even though Equatorial Guinea is rendered in cyan and Gabon is shown in light brown in the original color image. Additionally, the originally green area designating Somalia 130 and the originally pink area designating Kenya 134 appear to be one medium gray country in the prior art map of Africa 110. Similarly, the prior art image processor has united the dark yellow area for Zambia 142 and the taupe area designating Zimbabwe 146.

Referring to FIGURE 2, in a prior art black and white or single colorant rendition 210 of a color pie chart (not shown), first pie wedges 214, originally rendered in red, and second pie wedges 218, originally rendered in green, are rendered in the same shade of gray. Furthermore, originally yellow pie wedges 222 are rendered as white and have, therefore, entirely disappeared from the chart 210.

Referring to FIGURE 3, a method 310 of generating a single colorant version of a color image, which does not suffer from the problems described in relation to FIGURE 1 and FIGURE 2, includes a continuously variable screening tool generation step 314. As will be explained in detail below, a continuously variable screening tool is a tool for applying a unique modulation or texture to an image based on variation in some aspect of the image. For example, a continuously variable screening tool

associates a unique pattern to each unique hue and saturation in a color image. Each unique pattern is used as a substitute for color in a single colorant version of the color image. Of course, the definition of continuously variable depends on the architecture of the image processor on which the method is implemented. In purely analog image processing systems, the screening tool is continuously variable in the sense that the calculations required to generate the variable screening tool are carried out by analog multipliers, adders, comparators and the like. The infinite resolution provided by analog calculation generates a truly continuous screening tool. In digital image processors, continuity is judged in light of system resolution or quantization. Thus, in digital systems, the screening tool is continuous in the sense that there is a different screen pattern for every measurable or calculable hue and chromaticity in an image. In the continuous screening tool generation step 314, subtle differences in hue are reflected in subtle differences in screen pattern. Subtle changes in chromaticity or saturation are also reflected in subtle differences in screen pattern. The continuously variable screening tool can be predefined or it can be generated at run time. When generated at run time, screen patterns need only be calculated for colors that are present in an image being processed.

In an image transformation step 318, a single colorant description of a color image is created. It is to be appreciated that, preferably (and as described below), the generation step 314 and the transformation step 318 are sequentially performed on each pixel, on a pixel-by-pixel basis, such that the steps are repeated for each pixel. However, it would also be possible to first generate a screening tool for each pixel of the image, and then transform the image thereafter. The continuously variable screening tool is used to represent each hue and saturation with a unique pattern. Lightness is coded in, for example, the thickness or width of pattern components. As will be explained below, hue and chromaticity or saturation are coded, for example, as a mixture or blend of predefined patterns.

In a rendering step 322, media is marked as directed by the single colorant description of the image. Media includes any image-rendering medium. For example, media include paper, velum, and single color display devices such as, for example, black and white CRT's, Liquid Crystal Displays and monochrome monitors.

In one implementation of the method 310 for generating a single colorant

version of a color image, for calculation and analysis purposes, colors found in an image are located or mapped within a machine independent color space, such as, for example, the well known Commission International de l'Eclairage or International Commission on Illuminations L*a*b* color space (CIELAB). A plane sliced from the
5 CIELAB color space is depicted in FIGURE 4. Luminosity is indicated along an L* axis (not shown) through an origin or intersection of axes. The axes illustrated are labeled a^* and b^* . The L* axis extends into and out of the plane of the diagram. The a^* and b^* axes represent ranges of hue and saturation. A particular color P is located in the color space by its relationship to the three axes. For example, color P has a hue
10 angle Φ measured from, for example, from the a^* axis and a saturation σ , depicted as a radial distance from the origin. Color P is also associated with a luminance that is depicted as a height along the L axis. Changes in the luminance of P would move it to another luminance plane, either above or below the depicted plane. Also depicted in FIGURE 4 are a set of reference screens or screen cells including a neutral screen S_0
15 and a plurality of hue dependant primary screens $S_1...S_6$. The reference screens are a set of predetermined, related pattern primitives that are used in the continuous screening tool generation step 314 as the basis or seeds for generating the rest of the continuous screening tool. Six primary screens are shown, but any number of primary screens may be used. Typically, the primary screens are stored in memory.
20 Therefore, the number of primary screens used is a trade off between accuracy and calculation speed on the one hand and required memory on the other hand. The primary screens $S_1...S_6$ are shown as being evenly distributed around the outer edge of the color space. However, other distributions are possible. Primary screens are distributed in whatever manner is convenient for the purposes of performing blending
25 calculations. The neutral screen S_0 shown is a high frequency 45-degree dot screen constructed from the product of two cosine functions. However, it is contemplated that other screens are suitable. The primary screens $S_1...S_6$ are hue dependent. The reference screens $S_0...S_6$ are related to each other at least in as much as they have at least some maxima and minima in the same locations.

30 For example, the set of reference screens $S_0...S_6$ is generated from the equations and algorithms described in the following C source code, wherein:

period = Screencell Size; /*for example, 16/*
 periodDiv2 = period/2;
 amp = 127.5;
 c1 = 2.0 * 3.1416 / period;
 5 the index i and j goes from 0 to period-1;
 round(...) denotes rounding the argument to an integer; and
 rem(a,b) is the remainder of dividing a by b.

```

S0:neutral(i,j) = round(127.5 - amp *cos(c1*i) * cos(c1*j));  

10  

S1:red(i,j) = round(127.5 - amp*cos(c1*(j+i)));  

S3:green(i, j) = round(127.5 - amp*cos(c1*(j-i)));  

15 S6:magenta(i,j)= round(127.5 - amp*cos(c1*(j+i+4*sin(c1*j))));  

S4:cyan(i,j) = round(127.5 - amp*cos(c1*(i-j-4*sin(c1*j))));  

S5:blue(i,j) determined as follow:  

20           red = round(127.5 - amp*cos(c1*(j+i)));  

           green = round(127.5 - amp*cos(c1*(j-i)));  

           i1 = rem(i, period) - periodDiv2;  

           j1 = rem(j, period) - periodDiv2;  

           if(i1*j1 >=0)  

25           blue(i,i) = red;  

           else  

           blue(i,j) = green;  

S2: yellow(i,j) determined as follow:  

30           red = round(127.5 - amp*cos(c1*(j+i)));  

           green = round(127.5 - amp*cos(c1*(j-i)));  

           i1 = rem(i, period) - periodDiv2;  

           j1 = rem(j, period) - periodDiv2;
  
```

```
if(i1*j1 >=0)
    yellow(i,j) = green;
else
    yellow(i,j) = red;
```

5

Referring to FIGURE 5, numerical representations of the neutral screen S_0 and two primary screens S_1 and S_2 include threshold values **505** and relative dot position information **510**. The screens each contain threshold values **505** for two hundred fifty six dots. The dots correspond to pixels in an image. Furthermore, the dots correspond to dot or mark positions in a rendering of the image. In the screens, the dots are grouped in, for example 16×16 arrays or grids. Other screen sizes are acceptable and contemplated. FIGURE 5 includes column indexes **514** ranging from 1 to 16 and each screen is associated with a set of row indexes **518** ranging from 1 to 16. The relative dot position information is coded in the row **518** and column **514** indexes. In each screen S_0 , S_1 , S_2 , dot locations (1,9) and (9,1) hold maximum threshold values, namely 255. Furthermore, at dot location (9,9) each screen holds minimum threshold values, namely 0. Whatever screens are used, it is preferable that each screen in the set has at least one maximum in a dot location where the other screens also have a maximum. Likewise, it is preferable that each screen in a set has at least one minimum threshold value at a dot location where the other screens in the set also have minimums. Maintaining this relationship between screens helps ensure smooth transitions in patterns as colors across an image make subtle variations. For example, maintaining this relationship ensures that subtle variations in flesh tones are depicted as subtle variations in halftone texture.

The patterns in FIGURE 4 are created by comparing a reference value, for example 128, to the threshold values in the screens. For example, comparing a reference value to the thresholds in S_0 of FIGURE 5 and placing a mark at a corresponding dot location on a piece of paper wherever the reference value is above the threshold creates the pattern of S_0 of FIGURE 4. The center portion of each screen $S_0 \dots S_6$ is dark because the threshold value in the center of each screen is zero. Therefore, any reference value greater than zero is above the threshold in the center of the screen and a mark is placed in the dot location corresponding to the center of the

screen. Close inspection of FIGURE 5 reveals that the higher the reference value is, the more marks will be placed and the darker and thicker the pattern will be. This would be appropriate where the pixel value being compared to the screens is pixel darkness. However, typically the value being compared to a screen threshold value is
5 a pixel lightness or luminance, with increasing numerical values corresponding to brighter colors. Therefore, the sense of the marking operation is typically reversed with respect to the operation just described. In other words, typically marks are placed on print media when an image pixel value is below a screen threshold value. The result is that the patterns shown are inverted with respect to light and dark.

10 Examination of FIGURE 4 and FIGURE 5 also show that there are screens defined for only seven points in color space. While variations in lightness are accounted for automatically by the threshold patterns in the screens, there are still a multitude of colors for which screens are not defined. Those colors are accounted for, and the screen is made continuously variable by, calculating required screens, for
15 example, by an image processor at run time, by blending or interpolating between the reference screens $S_0 \dots S_6$. This process generates unique screens for hues and saturations not covered by the reference screens.

Any appropriate blending technique may be used. One technique is a two-step blending. First an intermediate or hue screen is calculated based on the equation:

20

$$\text{Screen_hue}(\Phi) = (1-\alpha) * S_k + \alpha * S_{k+1} \quad (1)$$

Where k and k+1 are primary screen numbers of screens near a color or hue of interest. The screen numbers k and k+1 are selected so that $\Phi_k < \Phi < \Phi_{k+1}$, where Φ is
25 the hue angle of the color of interest. α is a weighting factor. Linear or nonlinear weighting factors may be used. For example, α is calculated from the equation:

$$\alpha = (\Phi - \Phi_k) / (\Phi_{k+1} - \Phi_k) \quad (2)$$

30 Referring to FIGURE 4, a color P has a hue angle Φ located between the hue angles of S_1 and S_2 . Therefore, $\Phi_k < \Phi < \Phi_{k+1}$ is satisfied by k = 1. For example, $\Phi = 50$ degrees. $\Phi_k = 30$ degrees and $\Phi_{k+1} = 90$ degrees. Therefore

$$\alpha = (50 - 30) / (90 - 30) = 20/60 = 1/3 \quad (3)$$

and:

5

$$\begin{aligned} \text{Screen_hue}(\Phi) &= (1-(1/3)) * S_1 + (1/3) * S_2 \\ &= (2/3) * S_1 + (1/3) * S_2 \end{aligned} \quad (4)$$

The color **P** is located in color space one third of the way between locations associated
10 with **S₁** and **S₂**. Therefore, the intermediate hue screen calculation is automatically
weighted, by the structure of general equations (1) and (2), and as illustrated by
example equations (3) and (4), so that the influence of **S₁** is greater than the influence
of **S₂**.

Next, the intermediate screen (**Screen_hue**(Φ)) is blended with the neutral
15 screen. Again, a weighting factor is used. For example, a weighting factor based on
some function of saturation σ is used. Again, the weighting factor function can be
linear or non-linear. This second blending step makes texture variation based on color
saturation a component of the continuously variable screening tool. The neutral
screen / intermediate screen blending is achieved by, for example, the equation:
20

$$\text{Screen}(\Phi, \sigma) = (1-w(\sigma)) * S_0 + w(\sigma) * \text{Screen_hue}(\Phi) \quad (5)$$

Referring to FIGURE 6, an intermediate screen **610** includes a minimum at
location (9,9) and a maximum at locations (1,9) and (9,1). The intermediate screen
25 **610** is calculated based on equation (4). For example, with reference to FIGURE 5, in
primary screen **S₁** the threshold value at grid location (3,2) is 79. In primary screen **S₂**
the threshold value at grid or dot location (3,2) is 10. Applying equation (4) leads to:
 $(2/3)(79) + (1/3)(10) = 56$. Therefore, the threshold value in the intermediate screen
30 **610** at location (3,2) is 56. The same process is repeated, as required, for each grid or
dot location in the intermediate screen **610**. Likewise, a final blend screen **620** is
calculated based on equation (5) under the assumption that $w(\sigma) = 2/3$. For example,
with reference to FIGURE 5, in neutral screen **S₀**, the threshold value at grid location

(3,2) is 44. In the intermediate screen 610 the threshold value at grid or dot location (3,2) is 56. Applying equation (5) leads to: $(1/3)(44) + (2/3)(56) = 52$. Therefore, the threshold value in the final blend screen 620 at location (3,2) is 52. Again, the same process is repeated, as required, to calculate the threshold value for each grid or dot location in the final blend screen 620. It is noted that final blend screen 620 also includes a minimum at location (9,9) and a maximum at locations (1,9) and (9,1).

FIGURE 7 illustrates the blending operation of equations (4) and (5) and FIGURE 6 in graphical form. Primary screen S₁ 710 is multiplied by 2/3 and added to 1/3 of primary screen S₂ 714. The result of that calculation is an intermediate screen 718. Next, the neutral screen S₀ 722 is multiplied by 1/3 and added to 2/3 of the intermediate screen 718 resulting in a blend screen 726. Dark portions 730 of the cells 710, 714, 718, 722 represent low threshold values. Light portions 734 of the cells 710, 714, 718, 722 represent high threshold values. Gray portions 738 of the cells 710, 714, 718, 722 represent intermediate threshold values. The blending operation is quite clearly seen by examining primary screen S₁ 710, primary screen S₂ 714 and intermediate screen 718. In this example, a relatively heavy weighting factor of 2/3 multiplies primary screen S₁ 710. Therefore, the influence of primary screen S₁ 710 is quite strong in the intermediate screen 718. For example, the intermediate screen 718 and primary screen S₁ 710 both include three dark portions 730. The three dark portions in the intermediate screen 718, are generally in the same location and are approximately the same shape as the three dark portions 730 in primary screen S₁ 710. However, there are some important differences in the shape of the dark portions 730 in the intermediate screen 718. The influence of primary screen S₂ 714 on the intermediate screen 718 can be seen in these shape variations. For example, at points where primary screen S₂ 714 has dark portions 730 at grid or dot locations that correspond to gray portions 738 in primary screen S₁ 710, the intermediate screen has bulges or distortions in the dark portions 730. The influence of S₂ 714 is also apparent in gray regions 742 of the intermediate screen 718. The gray regions occur where dark portions 730 of primary cell S₂ 714 are blended with light portions of primary screen S₁ 710. Blending between the reference screens in a machine independent color space as described above generates a unique pattern corresponding to each unique color in the color space. As color changes from shade to shade, a new pattern is

created corresponding to each shade. A continuous rainbow or color sweep is transformed into a continuum of shifting patterns.

Referring to FIGURE 8, the original reference screens $S_0 \dots S_6$ are shown in relation to the rest of a continuously variable screening tool **810**. The continuously
5 variable screening tool **810** is represented by a small sample set of calculated screens generated with the blending equations described above. A blended screen **814** is located in the a^*b^* plane approximately in the same location as color P (see FIGURE 4). Therefore the blended screen **814** is very similar to the blended screen **620, 726** of FIGURE 6 and FIGURE 7.

10 While the described system varies the screen as a function of hue and saturation, continuously variable screening tools can be functions of other color description parameters. The choice is limited only by the parameters that describe the color space in which one chooses to work.

15 Any convenient screen dimension can be used. For example, screens containing screens with dimensions of 10 dots x 10 dots, 12 dots x 12 dots and 16 dots x 16 dots are common. Cell dimensions are chosen for the usual reasons of spatial and gray level resolution.

20 In operation, for example, during the image transformation step **318**, a color image can be thought of as being overlaid with an array of generic screens. This effectively assigns each pixel in the color image to a particular dot position within a screen. For example, some pixels are assigned dot or grid location (3,2). Other pixels are assigned dot location (9,9) and so on and so forth for all the available dot locations (depending on the size of the screens). Each pixel is analyzed and is associated with 25 one of the reference screens or with a screen that is calculated from an interpolation or blend of the reference screens (in, for example, step **314** for that pixel). For example, equation (1) and equation (5), described above, are used to calculate a screen for a pixel base on a hue and a saturation described by the pixel. A pixel value, for example, a pixel lightness or luminance, is then compared to the threshold value corresponding to the dot location assigned to the pixel. If the pixel value is below (or 30 above, depending on the system) the threshold value a mark will be placed on a media. Of course, the media can be any image storage device or rendering media. For example, a mark or bit can be set in an electronic storage device, a dot can be

printed on a piece of paper, or a pixel location can be made dark (or light) on a monochrome monitor. Of course, it is not necessary to generate an entire calculated screen. It is only necessary to calculate the threshold value associated with the dot location assigned to the pixel of interest. For example, if the pixel is assigned dot 5 location (3,2) then it is only necessary to use equations (1) and (5) to calculate a threshold value for dot location (3,2). Alternatively an entire screen may be calculated and stored for use with other similar pixels.

Indeed, any number of implementations are possible. Implementations range from memory intensive, continuous screening tool precalculation and look up table 10 generation and storage schemes, to a calculation intensive, on the fly screen calculation techniques. Image processors can range from analog and/or digital computer implementations to fuzzy logic or neural network implementation.

Referring to FIGURE 9, preferably, when an embodiment uses on the fly screen blending, blending is done one dot location at a time. For example, a pixel 15 address counter **914** generates an image address for an image pixel. A screen address generator **918** receives the image address and relates it to a screen dot location **510** using modular arithmetics. For example, a scanline number and a pixel position within a scanline are used to determine that the image pixel is related to, for instance, screen dot position (7,13). Where necessary, a color converter **922** is used to 20 determine convenient pixel values from available pixel values. For example, a^*b^* values of the image pixel addressed by the pixel address counter **914**, are converted to more convenient hue and saturation values. A set of primary screens **926** is accessed. As described in reference to equation (1), the pixel hue value is used to select two of the primary screens **926** for blending. Additionally, the screen dot location generated 25 by the screen address generator **918** is used to select appropriate screen threshold values from the selected screens. For example, the threshold values from dot locations (7,13) from both S_i and S_j are selected for blending in a first blender **930**. In FIGURE 9, those threshold values are denoted as v_i and v_j . As described in reference to equation (2), the pixel hue value is also used by the first blender **930**, to calculate 30 weighing factors for each of the selected screens. The screen dot location is used to select an appropriate screen threshold value from a neutral screen **934**. For example, the screen threshold value from location (7,13) of S_0 is selected for blending. In

FIGURE 9, that threshold value is denoted as v_0 . An intermediately blended threshold value is delivered from the first blender 930 to a second blender 938. As described in reference to equation (5), the pixel saturation value is used, by the second blender 938, to calculate weighing factors for the intermediate threshold value and the neutral screen S_0 threshold value. The output of the second blender is a final continuous screening tool threshold value. In FIGURE 9, the final continuous screening tool threshold value is denoted v . An image pixel luminance value L^* is compared to the final continuous screening tool threshold value in a comparator 942. The output of the comparator 942 is a binary output. The binary output indicates whether or not a mark is to be generated as the transform of the image pixel. This procedure is repeated for every image pixel in the image.

Referring to FIGURE 10, the method 310 of generating a single colorant version of a color image of FIGURE 3 is used to transform (step 318) the color map of Africa (not shown), mentioned in reference to FIGURE 1. The color map of Africa is rendered (step 322) as a textured black and white map of Africa 1010. In contrast to the prior art black and white map of Africa 110, in the textured map of Africa 1010 the Western Sahara 1014 is clearly distinguishable from Morocco 918. Furthermore, Equatorial Guinea 1022 is clearly separate from its neighbor Gabon 1026. Additionally, Somalia 1030 and Kenya 1034 are rendered with textures as distinct from one another as their original green and pink colors. Similarly, Zambia 1042 and Zimbabwe 1046 are properly rendered as separate countries.

Referring to FIGURE 11, in contrast to the prior art image processor, which failed to distinctly transform primary colors in the pie chart 210 shown in FIGURE 2, in a textured black and white pie chart 1110 first pie wedges 1114, created as red and second pie wedges 1118, created as green, are rendered with distinct patterns. Furthermore, originally yellow pie wedges 1122, which are not visible in the prior art pie chart 210, are clearly visible and rendered with a third pattern.

Referring now to FIGURE 12, an image processor 1210 operative to transform a multicolor image into a textured single colorant version comprises a continuously variable screening tool generator 1214. The continuously variable screening tool generator 1214 is operative to generate a different screen texture for every hue in the multicolor image. For example, the continuously variable screening

tool generator **1214** operates during the screen generation step **310**. Preferably, the continuously variable screening tool generator **1214** generates textures that are related to hue, so that similar hues are mapped to similar textures. Continuously variable screening tool generators are implemented in a wide variety of ways. One
5 continuously variable screening tool generator comprises a reference screen storage device **1218** and a screen blender **1222**. The reference screen storage device **1218** can be any convenient pattern storage mechanism. In an analog system, the reference screen storage device **1218** is, for example, a plurality test pattern generator circuits. Each test pattern generator circuit is configured to produce a different pattern. In a
10 digital system, the reference screen storage device **1218** is typically a microprocessor or computer memory. However, other implementations are possible. For example, the reference screen storage device **1218** can be a rotating media such as a hard disk or a CD ROM. Additionally, reference screens can be stored and retrieved over a communications link, such as, for example a computer network. As indicated above,
15 those skilled in the art will immediately understand that a screen blender **1222** can also be implemented in a wide variety of ways. In an analog system, a screen blender **1222** is, for example, comprised of a plurality of amplifiers and adder circuits. The gain of the amplifiers is varied in accordance with appropriate weighing factors in order to vary the contribution of the test pattern generation circuits being blended.
20 The adder circuits combine the thus modified test pattern signals to produce the blended screening signal. In digital systems, the blending equations described above are implemented in software modules. A microprocessor, digital signal processor, or other computing device executes the modules to examine color image pixels and select the appropriate reference screens. Additionally, the appropriate weighting
25 factors are calculated and applied to the selected reference screens. In other implementations, an application specific integrated circuit or programmable gate array is developed or configured to carry out some or all of the functions of the reference screen storage device **1218** and the screen blender **1222**. Alternatively, neural networks are trained to generate black and white screen patterns in response to color
30 pixel input stimulation.

The exemplary image processor **1210** further comprises an image transformer **1226**, a marker **1230** and a print engine **1234**. The image transformer is operative to

perform image transformation step 318. The image transformer 1226 receives an image 1238 and examines pixels that comprise the image. Where necessary, the image transformer 1226 first transforms the image into a color space that is compatible with the continuous screening tool. For example, the image transformer 5 may convert an image from an RGB color space to a CIELAB color space. The image transformer 1226 uses a location of a pixel within the image as well as pixel values from the pixel to address an appropriate screen and dot location within the continuous screening tool. The image transformer 1226 communicates with the continuous screening tool generator 1214 to retrieve a threshold value from the addressed dot 10 location. For example, the image transformer 1226 uses a hue angle value from the pixel to address a screen and uses a pixel location within the image to address a dot location. The image transformer 1226 compares the retrieved threshold value with a pixel value from the pixel and determines whether or not a mark should be placed for the pixel. For example, the image transformer compares a pixel lightness with the 15 retrieved threshold. The image transformer 1226 repeats this process for every pixel in the image to generate a single colorant version of the image that preserves color information in the form of texture.

The foregoing image transformer description is directed toward a digital implementation. However, image transformers can be implemented in any number of ways. For example, in one analog implementation of an image transformer, a screen signal, generated by an analog continuously variable screening tool generator, is delivered to a first input of a comparator circuit and used as a reference. An image signal, synchronized to the screening signal, is delivered to a second input of the comparator circuit. The comparator circuit outputs a mark signal based on a 20 comparison between the signals on the two inputs of the comparator. 25

In general, the single colorant version of the image is passed to the marker 1230. The marker 1230 is a print engine controller. The marker 1230 uses the single colorant version of the image as a basis for sending mark signals to the print engine 1234. Typically, the marker 1230 is particularly adapted to communicate with and 30 control a particular kind of print engine 1234.

The print engine 1234 can be any image-rendering device. Preferably the print engine 1234 is a single colorant image-rendering device, such as, for example, a black

and white xerographic printer. A xerographic printer is known by those skilled in the art to comprise, for example, a fuser, a developer, and an imaging member. Alternatively, the print engine 1234 may include any other image-rendering device, such as, for example, an ink jet printer, a cathode ray tube, a monochrome monitor, or
5 a laser printer.

In some implementations, the functions of the continuously variable screening tool generator 1214, image transformer 1226 and marker 1230 are combined or performed by other devices. The architecture illustrated in FIGURE 12 is only exemplary and is not meant to limit the invention. For example, as described above,
10 in some analog implementations a comparator provides the majority of the functions of an image transformer and a marker.

The invention has been described with reference to particular embodiments. Modifications and alterations will occur to others upon reading and understanding this specification. For example, the invention can be implemented using a color space
15 other than the CIELAB color space. More or fewer reference screens can be used. Other reference screen patterns can be used. Reference screens do not have to be distributed about the outer edge of the color space. Blending or interpolation can be based on parameters other than hue angle and saturation. Many other image processor implementations are contemplated for using a continuously variable screening tool to
20 generate single colorant versions of color images. Hardware, software, neural networks, application specific integrated circuits, programmable gate arrays and a host of other technologies can be used to implement versions of the image processor. It is intended that all such modifications and alterations are included insofar as they come within the scope of the appended claims or equivalents thereof.

CLAIMS

What is claimed is:

1. A method for rendering an image described in a multi-colorant color space, in a single-colorant color space, the method comprising:

generating a continuously variable screening tool operative to provide a texture corresponding to each hue and saturation in the multi-colorant color space,
5 and

transforming the multi-colorant description of the image based on the continuously variable screening tool thereby creating a single-colorant description of the image.

2. The method for rendering an image of claim 1 wherein the step of generating a continuously variable screening tool further comprises:

defining a neutral screen associated with neutral color;

5 defining a plurality of primary screens associated with a plurality of hues from the multi-colorant color space.

3. The method for rendering an image of claim 2 further comprising the step of generating a set of blended screens associated with a set of remaining hues by performing a weighted blend between nearby screens.

4. The method for rendering an image of claim 3 wherein the step of generating a set of blended screens further comprises blending between two primary screens to generate an intermediate screen $\text{screen_hue}(\phi)$ using the equation:

$$\text{Screen_hue}(\Phi) = (1-\alpha) * S_k + \alpha * S_{k+1}$$

5 where Φ is a hue angle of a pixel being transformed, k is an index indicating one of the primary screens, $k+1$ indicates another primary screen such that $\Phi_k < \Phi < \Phi_{k+1}$, where Φ_k and Φ_{k+1} are hue angles associated with the primary screens S_k and S_{k+1} respectively and where

$$\alpha = (\Phi - \Phi_k) / (\Phi_{k+1} - \Phi_k).$$

5. The method for rendering an image of claim 4 wherein the step of generating a blended screen further comprises blending between a neutral screen and the intermediate screen Screen_hue(Φ) to generate a blended screen screen(Φ, σ) using the equation:

$$5 \quad \text{screen}(\Phi, \sigma) = (1-w(\sigma))S_0 + w(\sigma) \text{Screen_hue}(\Phi)$$

where S_0 is the neutral screen, and $w(\sigma)$ is a function of saturation σ having a value between 0 and 1.

6. The method for rendering an image of claim 3 wherein the step of generating a blended screen further comprises blending between a primary screen and the neutral screen.

7. The method for rendering an image of claim 1 wherein the step of generating a single-colorant version of the image further comprises marking media as directed by the single-colorant description of the image.

8. The method for rendering an image of claim 7 wherein the step of marking media further comprises comparing a luminance of a pixel from the image with an associated screen value and placing a mark on the media if the luminance value is above the screen value.

9. The method for rendering an image of claim 7 wherein the step of marking media further comprises comparing a luminance of a pixel from the image with an associated screen value and placing a mark on the media if the luminance value is below the screen value.

10. The method for rendering an image of claim 2 wherein the step of defining a neutral screen further comprises generating a screen based on the product of two cosine functions.

11. The method for rendering an image of claim 2 wherein the step of generating a neutral screen further comprises generating a high frequency dot screen.

12. The method for rendering an image of claim 2 wherein the step of generating a neutral screen further comprises generating a forty-five degree high frequency dot screen.

13. The method for rendering an image of claim 2 wherein the step of generating a plurality of primary screens further comprises generating a plurality of hue dependent screens, each of the plurality of screens having at least one common dot location for a maxima and at least one common dot location for a minima.

14. An image processor operative to render a single colorant version of a multicolor image, the image processor comprising:

a continuously variable screening tool generator operative to generate a different screen texture for every hue and saturation in the multicolor image.

15. The image processor of claim 14 wherein the image processor is a reprographic image processor.

16. The image processor of claim 14 wherein the image processor is a general-purpose computing device.

17. The image processor of claim 14 wherein the image processor is a business graphic authoring device.

18. The image processor of claim 14 wherein the continuously variable screening tool generator further comprises:

a reference screen storage device operative to store a set of predetermined reference screen patterns in association with locations within a color space; and

a screen blender operative to access the screen storage device and use the reference screens to calculate screen patterns for colors in the multicolor image that do correspond to locations in the color space that are different than the locations in the color space associated with the reference screens.

19. An image processor operative to render a single colorant version of a multicolor image, the image processor comprising:

a print engine;

a continuously variable screening tool generator operative to generate a

5 different screen texture for every hue and saturation in the multicolor image;

an image transformer operative to apply the different generated screen textures in transforming the multicolor image to generate a single colorant version of the image;

10 a marker operative to use the single colorant version of the image as a basis for controlling the print engine to render the single colorant version of the image.

20. The image processor of claim 20 wherein the print engine is a xerographic printer.

COLOR TO BLACK AND WHITE CONVERTER

ABSTRACT

A continuously variable screening tool is used to generate a unique texture pattern for every color in a multicolor image. The continuously variable screening tool allows a single colorant version of the image to be generated with less information loss than typically suffered in the multicolor to single color
5 transformation process. The continuously variable screening tool is generated by blending patterns from a set of reference screens. The reference screens are associated with selected reference colors in, for example, a machine independent color space. A calculated screen is generated through a weighted blend of reference screens located near the arbitrary color in the machine independent color space.
10 Typically, the weights depend on the distance the arbitrary color is from each of the reference colors. The screens consist of arrays of threshold values. Each threshold value is associated with a dot position and an image pixel. Where a pixel value exceeds the associated threshold value, provision is made to place a mark in the associated dot position. An image processor operative to carry out the method
15 comprises a continuously variable screening tool generator. An embodiment of the image processor includes a reference screen storage device and a screen blender.

C:\DATA\UDD\APPSJDD\XER20329.APP.DOC

பாரிசு மீட்டர் கோமென்ஸ்

110

118

114




FIGURE 2 (Pavon Ant.)

DAIRY REVENUE COMPARED TO TOTAL SALES




FIGURE 2 (Prior Art)

FIGURE 3





FIGURE 4



卷之三

10

1

| Intermediate | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
|--------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1 | 0 | 10 | 24 | 56 | 97 | 143 | 176 | 218 | 245 | 255 | 245 | 218 | 176 | 128 | 79 | 37 |
| 2 | 2 | 3 | 37 | 56 | 84 | 120 | 157 | 189 | 212 | 222 | 242 | 245 | 218 | 176 | 128 | 79 |
| 3 | 4 | 4 | 79 | 97 | 120 | 145 | 166 | 182 | 189 | 187 | 176 | 128 | 79 | 37 | 10 | 0 |
| 4 | 5 | 5 | 127 | 143 | 157 | 166 | 170 | 166 | 157 | 143 | 127 | 79 | 37 | 10 | 0 | 37 |
| 5 | 6 | 6 | 176 | 187 | 189 | 182 | 166 | 145 | 120 | 97 | 79 | 37 | 10 | 0 | 10 | 79 |
| 6 | 7 | 7 | 218 | 222 | 189 | 157 | 120 | 85 | 56 | 37 | 10 | 0 | 10 | 37 | 79 | 127 |
| 7 | 8 | 8 | 245 | 242 | 222 | 187 | 143 | 97 | 56 | 24 | 10 | 0 | 10 | 37 | 79 | 127 |
| 8 | 9 | 9 | 255 | 245 | 218 | 176 | 127 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 176 |
| 9 | 10 | 10 | 245 | 218 | 176 | 128 | 79 | 37 | 10 | 0 | 10 | 24 | 56 | 97 | 143 | 187 |
| 10 | 11 | 11 | 218 | 176 | 128 | 79 | 37 | 10 | 0 | 10 | 37 | 56 | 84 | 120 | 157 | 189 |
| 11 | 12 | 12 | 176 | 128 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 97 | 120 | 145 | 166 | 189 |
| 12 | 13 | 13 | 176 | 128 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 143 | 157 | 166 | 189 |
| 13 | 14 | 14 | 128 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 176 | 187 | 189 | 182 | 166 |
| 14 | 15 | 15 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 176 | 218 | 222 | 212 | 189 | 157 |
| 15 | 16 | 16 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 176 | 218 | 245 | 218 | 222 | 187 | 97 |
| 16 | 17 | 17 | 10 | 0 | 10 | 37 | 79 | 127 | 176 | 218 | 245 | 218 | 222 | 187 | 97 | 56 |

620

| | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 0 | 37 | 79 | 127 | 176 | 218 | 245 | 255 | 245 | 218 | 176 | 128 | 79 | 37 |
| 10 | 22 | 52 | 92 | 137 | 182 | 218 | 240 | 245 | 224 | 187 | 143 | 95 | 52 |
| 37 | 52 | 77 | 111 | 147 | 180 | 205 | 218 | 187 | 149 | 106 | 67 | 37 | 21 |
| 79 | 92 | 111 | 133 | 153 | 170 | 180 | 182 | 176 | 143 | 106 | 73 | 49 | 36 |
| 127 | 137 | 147 | 153 | 156 | 153 | 147 | 138 | 127 | 95 | 67 | 49 | 42 | 21 |
| 176 | 182 | 180 | 170 | 153 | 133 | 111 | 92 | 79 | 52 | 37 | 36 | 49 | 21 |
| 218 | 218 | 205 | 182 | 147 | 111 | 78 | 52 | 37 | 21 | 21 | 37 | 67 | 106 |
| 245 | 240 | 218 | 182 | 138 | 92 | 52 | 22 | 10 | 6 | 21 | 52 | 95 | 142 |
| 255 | 245 | 218 | 176 | 127 | 79 | 37 | 10 | 0 | 10 | 37 | 79 | 127 | 176 |
| 245 | 224 | 187 | 143 | 95 | 52 | 21 | 6 | 10 | 22 | 52 | 92 | 137 | 182 |
| 218 | 187 | 149 | 106 | 67 | 37 | 21 | 21 | 37 | 52 | 77 | 111 | 147 | 180 |
| 176 | 143 | 106 | 73 | 49 | 36 | 37 | 52 | 79 | 92 | 111 | 133 | 153 | 170 |
| 128 | 95 | 67 | 49 | 42 | 49 | 67 | 95 | 127 | 137 | 147 | 153 | 156 | 147 |
| 79 | 52 | 37 | 36 | 49 | 73 | 106 | 142 | 176 | 182 | 180 | 170 | 153 | 111 |
| 37 | 21 | 21 | 37 | 67 | 106 | 148 | 187 | 218 | 218 | 205 | 180 | 147 | 111 |
| 10 | 52 | 52 | 52 | 95 | 142 | 187 | 224 | 245 | 240 | 218 | 182 | 138 | 92 |

FIGURE 6

三

the first time, and the author's name is given in the title.





FIGURE 7



→ 810




FIGURE 8




FIGURE 9







FIGURE 10

DAIRY REVENUE COMPARED TO TOTAL SALES



WESTERN REGION



EASTERN REGION

FIGURE 11

1210




FIGURE 12

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Attorney's Docket No. XER 2 0329
D/A0125

As a below inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

COLOR TO BLACK AND WHITE CONVERTER

the specification of which

X is attached hereto OR _____ was filed on
Application Serial No.
and was amended on (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

(Number) (Country) (Filing Date)

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Prior Provisional U.S. Patent Application(s):

(Application Serial No.) (Filing Date)

I hereby claim the benefit under Title 35, United States, Section 120 of any United States application(s) or any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information which is material to patentability as defined in Title 37, of Federal Regulations Code, Section 1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Patent Application(s):

(Application Serial No.) (Filing Date) (Status)
(patented, pending, abandoned)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

| | | | |
|---|--|---|--|
| Steven M. Auvil, Brian G. Bembenick Joseph D. Dreher, Jude A. Fry, W. Scott Harders, Richard M. Klein, Sandra M. Koenig, Scott A. McCollister, Richard J. Minnich, Philip J. Moy, Patrick R. Roche, Albert P. Sharpe, III, Mark S Svat, Richard B. Domingo Mark Costello Lloyd F. Bean, II | Reg. No. 40,492 Reg. No. 41,463 Reg. No. 37,123 Reg. No. 38,340 Reg. No. 42,629 Reg. No. 33,000 Reg. No. 33,722 Reg. No. 33,961 Reg. No. 24,175 Reg. No. 31,280 Reg. No. 29,580 Reg. No. 19,879 Reg. No. 34,261 Reg. No. 36,784 Reg. No. 31,342 Reg. No. 37,775 | Mark E. Bandy, John P. Cornely, Christopher B. Fagan, Steven M. Haas, Michael E. Hudzinski, Thomas E. Kocovsky, Jr., Brian E. Kondas, James W. McKee, Jay F. Moldovanyi, Timothy E. Nauman, Jim Scarbrough R. Scott Speroff, John E. Beck Henry Fleischer Eugene O. Palazzo | Reg. No 35,788 Reg. No. 41,687 Reg. No. 22,987 Reg. No. 37,841 Reg. No. 34,185 Reg. No. 28,383 Reg. No. 40,685 Reg. No. 26,482 Reg. No. 29,678 Reg. No. 32,283 Reg. No. 47,056 Reg. No. 37,450 Reg. No. 22,833 Reg. No. 25,582 Reg. No. 20,881 |
|---|--|---|--|

SEND CORRESPONDENCE TO:

Albert P. Sharpe, III, Esq.
Fay, Sharpe, Fagan,
Minnich & McKee, LLP
1100 Superior Avenue, 7th Floor
Cleveland, OH 44114-2518

DIRECT TELEPHONE CALLS TO:

(name and telephone number)

Albert P. Sharpe, III
(216) 861-5582

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of first joint inventor: Ying-wei Lin

Inventor's Signature: Ying-wei Lin

Date: 10/26/2000

Residence: Penfield, New York

Country of Citizenship: U.S.A.

Post Office Address:

119 Hillrise Drive
Penfield, New York 14526

Full name of second joint inventor: Jeng-nan Shiau

Inventor's Signature: Jeng-nan Shiau

Date: 10/26/2000

Residence: Webster, New York

Country of Citizenship: U.S.A.

Post Office Address:

687 Shadow Wood Lane
Webster, New York 14580